

# Granville FS-PX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Granville FS-PX 0W/30 is a fully synthetic mid-SAPS engine oil specially formulated to meet the very latest specifications and fuel efficiency targets required by Peugeot/Citroen power units including Blue HDi and Pure Tech engine types. Suitable for use in Petrol and Diesel engines where specified.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2  
PSA: B71 2312



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \* Fully synthetic
- \* Reduces fuel consumption
- \* Stable lubricant film at high temperatures
- \* Suitable for extended oil drain intervals

## PRODUCT USAGE

For use in engines where this viscosity and specification is required including petrol and diesel engines including those fitted with three way catalysts and diesel particulate filters.

## DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SIZE	PART NO	BARCODE
1 Litre	0892	5020618008927
5 Litre	0893	5020618008934
20 Litre	0894	5020618008941
199 Litre	0900	5020618009009



# Granville FS-PX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Clear amber liquid

**Odour** : Characteristic

**Solubility** : Insoluble in water

**Percentage of Biodiesel** : Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	9.76
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.46
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			52.22
Density	ASTM D792	@ 15°C			0.847

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

