

## Granville FS-NX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville FS-NX 0W/30 is a highly advanced fully synthetic engine oil formulated to give the most advanced protection and performance under all operating conditions giving increased fuel economy and extended service intervals. FS-NX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

Note: Not suitable for engines with 2 or 3 turbochargers.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2

BMW: LL-12 FE

### PRODUCT BENEFITS

\*Increased fuel economy

\*Extended service intervals

### PRODUCT USAGE

Not suitable for engines with 2 or 3 turbochargers

### DIRECTIONS FOR USE

Use as per manufacturer's recommendations

### STORAGE INSTRUCTIONS

Store sealed in a cool, dry place out of the reach of children.



\* Image for illustrative purposes only.

| SIZE      | PART NO | BARCODE       |
|-----------|---------|---------------|
| 1 Litre   | 1059    | 5020618010593 |
| 5 Litre   | 1060    | 5020618010609 |
| 20 Litre  | 1061    | 5020618010616 |
| 199 Litre | 1064    | 5020618010647 |



# Granville FS-NX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## SHELF LIFE

5 years from date of manufacture

|                                |                      |
|--------------------------------|----------------------|
| <b>Appearance</b>              | : Amber liquid       |
| <b>Odour</b>                   | : Characteristic     |
| <b>Solubility</b>              | : Insoluble in water |
| <b>Percentage of Biodiesel</b> | : Nil                |

| Test                         | Method     | Unit               | Min. | Max.  | Typical |
|------------------------------|------------|--------------------|------|-------|---------|
| Kinematic Viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.3  | <12.5 | 9.94    |
| Cold Cranking Viscosity      | ASTM D4684 | mPa.s              |      | 6200  |         |
| Total Base Number            | ASTM D2896 | mg KOH/g           | 7    |       | 7.98    |
| HTHS Viscosity               | ASTM D4683 | mPa.s              | 2.9  | <3.5  |         |
| NOACK Volatility             | ASTM D5800 | %                  |      | 11    |         |
| Kinematic Viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s |      |       | 54.84   |
| Density                      | ASTM D792  | @ 15°C             |      |       | 0.845   |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

