

Granville Hypafarm SUTO 15W/30

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypafarm SUTO 15W/30 is a high quality multi-functional agricultural oil ideally suited for older applications. The combination of specially selected additives and base oils enable this product to be used in petrol and diesel engines both naturally aspirated and turbo charged as well as transmission and hydraulic applications. Suitable for use in oil immersed braking systems.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: CF-4, GL-4 & SF

Case: MS1206

Massey Ferguson: M1135 & M1139

New Holland: 82009202

Allison: C4

CAT: TO-2

Ford: WSS-M2C134-D, WSS-M2C159B, WSS-M2C159C,

WSS-M2C86-A & WSS-M2C86-B

ZF: TE-ML-03A, TE-ML-05, TE-ML-06A & TE-ML-07D



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6500	5020618065005
199 Litre	6502	5020618065029

PRODUCT BENEFITS

*High quality additives and base oils

*Superior level of protection

PRODUCT USAGE

For use where this specification and type of oil is required

DIRECTIONS FOR USE

Use as per recommendations by the component manufacturer



Granville Hypafarm SUTO 15W/30

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	
Cold Cranking Viscosity	ASTM D4684	mPa.s		7000	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

