

## Granville EV-16 0W/16

1 Litre, 5 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville EV-16 0W/16 is a low viscosity fully synthetic engine oil specially formulated for use in hybrid-electric (H.E.V) plug-in hybrid vehicles (P.H.E.V) where this grade and specification of engine oil is recommended. This low viscosity oil is suitable for petrol engines, turbocharged or naturally aspirated with direct or indirect injection, is compatible with catalytic converters. Protects against low speed pre-ignition (LSPI). Refer to the owner's manual to ensure correct application.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SP RC  
ILSAC: GF-6B

### PRODUCT BENEFITS

- \* Low viscosity fully synthetic engine oil
- \* Excellent fuel economy
- \* Protects against low speed pre-ignition (LSPI)

### PRODUCT USAGE

Where recommended by the engine manufacturer

### DIRECTIONS FOR USE

Use as per manufacturer's recommendations

### STORAGE INSTRUCTIONS

Store upright in a cool dry place out of the reach of children



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1186	5020618011866
5 Litre	1187	5020618011873
199 Litre	1189	5020618011897



# Granville EV-16 0W/16

1 Litre, 5 Litre & 199 Litre

## SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Base Oil</b>	: 80
<b>Percentage of Biodiesel</b>	: Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.1	<8.2	
Cold Cranking Viscosity	ASTM D4684	mPa.s		<6200	
Total Base Number	ASTM D2896	mg KOH/g	8		
HTHS Viscosity	ASTM D4683	mPa.s	2.3		
NOACK Volatility	ASTM D5800	%		15	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

