

## Granville FS-G 5W/30

1 Litre, 5 Litre & 20 Litre

### PRODUCT DESCRIPTION

Granville FS-G 5W/30 is formulated primarily to meet the latest GM longlife requirements using the most advanced additive technology to produce a fuel efficient engine oil that has excellent high and low temperature performance and exceptional long term anti wear characteristics. Suitable for use in petrol & diesel engines where specified including: Vauxhall, Opel, Mercedes, BMW and Saab.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4

GM: LL-A-025 & LL-B-025

Opel: B-040-2095 & B-040-2098

MB: 229.3

BMW: LL-01 & LL-98

VW: 502.00 & 505.00

API: SL/CF



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	2402	5020618024026
5 Litre	2403	5020618024033
20 Litre	2408	5020618024088

### PRODUCT BENEFITS

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### PRODUCT USAGE

For engines where this specification and viscosity of lubricant is required.

### DIRECTIONS FOR USE

As recommended by the engine manufacturer.



# Granville FS-G 5W/30

1 Litre, 5 Litre & 20 Litre

## STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children.

## SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Biodiesel</b>	: Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	
Cold Cranking Viscosity	ASTM D4684	mPa.s		<6600	
Total Base Number	ASTM D2896	mg KOH/g	10		
HTHS Viscosity	ASTM D4683	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		10	
Pour Point	ASTM D97	°C		-27	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

